

RTX datum ATTACHMENTS



- Manual angling – left or right.
- Heavy duty steel construction.
- Heavy duty castors.
- Rear '3 point linkage' mounting.
- Parking stand.
- Quick change brush.
- Choice of brush bristle.
- Choice of 2 sweeping widths.
- **HYD**
- High torque direct drive motor.
- Relief valve motor protection.
- Reversible brush drive.
- Single hydraulic service operation
- **PTO**
- Powerful PTO drive

Combining robust construction with sheer sweeping power, the RTX makes light work of any sweeping task. This versatile unit is tractor '3 point linkage' mounted, hydraulic or PTO driven and available in two sweeping widths to meet your exact requirements. HYD models feature a reversible high torque hydraulic drive motor with a pressure relief valve to protect the motor seals. All units have integrated parking stands for storage and servicing when not in use.



Model	Mount	Sweeping width	Width	Depth	Height
RTX-240 HYD	Rear	2.35m	2.63m	1.3m	1.08m
RTX-200 HYD	Rear	1.95m	2.23m	1.3m	1.08m
RTX-240 PTO	Rear	2.35m	2.55m	1.3m	1.08m
RTX-200 PTO	Rear	1.95m	2.15m	1.3m	1.08m



Specification

Use:	Heavy – Extra heavy duty sweeping.
Mounting:	Tractor rear '3 point linkage' CAT 2.
Power Source:	PTO or HYD: 40–70 litre/min flow rate @ min 140 BAR.
Brush Adjust:	Heavy duty, height adjustable castor wheels.
Brush Spec:	560mm Diameter : Poly, or Poly/wire mix.
Angling:	Manual. 20 degrees left or right.
Castors:	203mm Diameter. Heavy duty.
Drive HYD:	Reversible high torque motor - relief valve protection.
Drive PTO:	PTO Input - gearbox and chain drive.



Tel: 01388 604029

Fax: 01388 663392

www.datumattachments.com

Email: info@datumattachements.com